

Neutra Zymes (CC109N)

Enzyme Treatment for Organic Waste

LABEL INFORMATION

Neutra Zymes Enzyme Treatment for Organic Waste

NEUTRA ZYMES enzymatic treatment for organic waste contains powerful waste-digesting, bacteria producing enzymes to break down organic material into water soluble nutrients. The bacteria digest the released nutrients, multiply and continue to produce enzymes to continually clean and deodorize areas with organic waste. Neutra Zyme may be used to remove pet stain odors other fabrics, trash odor, urine, and other organic-based odors from carpeting, upholstery, and other fabrics.

Benefits include: Non-Toxic | Neutral Fragrance | Safe For All Types Of Plumbing | Will Not Harm Carpeting | Upholstery Or Other Textiles

USE ON

- Organic Waste
- Grease
- Food
- Urine
- Trash
- Sewer

USE IN

- RV Holding Tanks
- Offices
- Hotels/Motels
- Restrooms
- Trash Chutes
- Kennels
- Lift Stations

USE FOR

- Odor Control
- Clearing Grease Traps
- Cleaning Drain Lines
- Cleaning Trash Chutes
- Cleaning Restrooms

DIRECTIONS

SHAKE/STIR WELL BEFORE USE

GENERAL ODOR CONTROL: To eliminate odor caused by vomit, spoiled food, decomposed animals, waste receptacles, etc., spray directly on malodor and allow bacterial action to work. The added fragrance will quickly neutralize any odor.

RESTROOM CLEANING: Mix 4 ounces of product per quart (32 oz) of water. Spray bathroom tile walls from the waist down, spray in and around Toilets and Urinals to kill urine and other odor causing bacteria, spray in trash cans. Poor down restroom floor drains to eliminate sewer gas odors.

CARPET DEODORIZING AND ORGANIC WASTE:

Mix 1/2 to 1 pint of product per-gallon of water. Apply with pump or trigger sprayer. Allow to remain moist for 30 minutes. Repeat if necessary. May be used with all types of carpet cleaning equipment and methods.

GREASE TRAPS: Pour directly into sink or pipe closest to trap, typically at night. Flush down with a cup of lukewarm water. Use 4-5 oz daily for traps less than 20 cubic feet. For larger traps, use 8-10 oz daily.

PORTA-TOILETS: Directly add 1 gallon and cover the solids with water. Repeat each time toilet is pumped.

SEPTIC TANKS: Add 1 pint per 25 cubic feet for initial treatment. Then use 8 oz. per week. Pour directly into toilet. If tank is clogged and odorous, add 1 gallon directly through manhole.

DRAIN LINES AND DOWN PIPES: Use 4 oz. for each 2 inches of pipe, 2-4 times weekly.

RECREATIONAL VEHICLES: Initially use 2 oz. per gallon of water. Maintain at 1 oz. per gallon of water. For use at a sump-station; use 1 gallon per 50 gallons tank capacity. Maintain at 1 pint per week.



PACKING INFORMATION

Available in
12x1(qts) | 4x1(gal) | 5 gal pail | 55 gal drum

SPECIFICATIONS

- Odor: Neutral
- Physical state: Milky liquid
- Color opaque white
- pH: 7.5
- Flammability (solid, gas): n/a
- Solubility: 100%
- Viscosity: n/a
- Detergency: mild
- Evaporation rate: <1
- Specific gravity: 1.005 @ 77°F
- Boiling point: 212°F
- %Volatile by volume: 100%
- Storage stability: 1 year+
- Cold stability: 32°F
- Vapor density: >2