Maui Zymes (cc139)

Enzymatic Treatment for Organic Waste

LABEL INFORMATION

Maui Zymes

Enzymatic Treatment for Organic Waste

MAUI ZYMES enzyme treatment for organic waste contains powerful waste-digesting, bacteria-producing enzymes to break down organic material into water soluble nutrients. The bacteria digest the released nutrients, multiply and continue producing enzymes to continually clean and deodorize areas where organic waste is present. May be used to remove pet stain odors, trash odor, and urine, and other organic-based odors from carpeting, upholstery, and other fabrics. Contains 300 billion cfu per gallon of the following: bacillus subtilis, bacillus amuloliquifaciens, bacillus lichenformis, bacillus megatherium, and pseudomonal.

USE ON

- Organic Waste
- Grease
- Food
- Trash Sewer
- Urine

USE IN

- RV Holding Tanks
- Kennels
- Hospitals
- Offices
- Restrooms
- Trash Chutes
- Lift Stations

USE FOR

- Odor Control
- Clearing Grease Traps
- Clearing Drain Lines
- Clearing Restrooms
- Clearing Trash Chutes



PACKING INFORMATION

Available in 4x1 gallons, 5 gallon pails, & 55 gallon drums

FEATURES & BENEFITS

Non-Toxic | Maui Fragrance | Safe for all types of plumbing | Will not harm carpeting, upholstery, or other textiles

DIRECTIONS

SHAKE/STIR WELL BEFORE USE.

GENERAL ODOR CONTROL: To eliminate odor caused by vomit, spoiled food, decomposed animals, waste receptacles, etc., spray directly on malodor and allow bacterial action to work. The added fragrance will quickly neutralize any odor.

RESTROOM CLEANING: Mix 4 ounces of product per quart (32 oz) of water. Spray bathroom tile walls from the waist down, spray in and around Toilets and Urinals to kill urine and other odor causing bacteria, spray in trash cans. Poor down restroom floor drains to eliminate sewer gas odors.

CARPET DEODORIZING AND ORGANIC WASTE: Mix 1/2 to 1 pint of product per gallon of water. Apply with pump or trigger sprayer. Allow to remain moist for 30 minutes. Repeat if necessary. May be used with all types of carpet cleaning equipment and methods.

GREASE TRAPS: Pour directly into sink or pipe closest to trap, typically at night. Flush down with a cup of lukewarm water. Use 4-5oz. daily for traps less than 20 cu. ft. For larger traps, use 8-10 oz. daily. PORTA-TOILETS: Directly add 1 gallon and cover the solids with water. Repeat each time toilet is pumped.

SEPTIC TANKS: Add 1 pint per 25 cu. ft. for initial treatment. Then use 8oz. per week. Pour directly into toilet. If tank is clogged and odorous, add 1 gallon directly through tank manhole.

DRAIN LINES AND DOWN PIPES: Use 4 oz. for each 2 inches of pipe size 2-4 times weekly. RECREATIONAL VEHICLES: Initially use 2 oz. per gallon of water. Maintain at 1 oz. per gallon of water. For use at a dump station, use 1 gallon per 50 gallons tank capacity. Maintain at 1 pint per week. CERTIFIED SALMONELLA AND E. COLI FREE

SPECIFICATIONS

Form: Liquid Color: milky white Flash Point: n/a Odor: Maui Boiling Point: 212°F

Freezing point: n/a Solubility in Water: soluble

Vapor density: 1

Wetting Ability: Excellent

pH: 8.5

Storage Stability: 1 Year +

Viscosity: n/a Cold Stability: 32° F Evaporation Rate: n/a Biodegradability: n/a



Phone: 713-838-1144 Toll Free 1-844-838-8224 ecommsales@competitivechoice.net