

# Elite 22 (CC185\_5PL)

## High Solids Extreme Performance Coating

### LABEL INFORMATION

#### Elite 22

ELITE 22 is an extreme performance floor coating that combines deep gloss, high durability and ease-of-use into one product. High molecular weight acrylic polymers and dense cross-linking produce a beautiful, long lasting shine that resists black marking and scuffing. Elite 22 is ideal for limited maintenance settings such as classrooms, patient rooms, and offices. It also responds to occasional burnishing – making it suitable for retail establishments, hallways and other frequently maintained areas.

#### USE ON

- Vinyl
- Rubber
- Linoleum
- Terrazzo
- Quarry Tile
- Sealed Concrete Floors

#### USE IN

- Schools
- Hospitals
- Apartments
- Offices
- Athletic Clubs
- Nursing Homes
- Restaurants

#### USE FOR

- Gloss floor coating
- Burnishing



### FEATURES & BENEFITS

Combines deep gloss, high durability and ease-of-use into one product | High gloss acrylic polymers produce a beautiful, long-lasting shine to reduce maintenance | Non-yellowing, low maintenance formula offers excellent black mark and scuff resistance

### PACKING INFORMATION

Available in  
4x1 & 5 Gallon

### DIRECTIONS

**APPLICATION:** 1. Strip floors to remove old waxes, sealers and finishes. 2. Rinse thoroughly and let dry. 3. With clean equipment apply thin, even coats of finish. 4. Under normal conditions, allow to dry for 30 minutes between coats. 5. For best results, apply a maximum of 4 coats in 24 hours.

**COVERAGE:** One gallon covers up to 3,000 square feet (1 liter covers 75 m<sup>2</sup>).

**MAINTENANCE:** 1. Daily: Sweep or dust mop as necessary to remove gritty soil. 2. Dirty Floors: Clean with 2-4 oz. of Neutrum floor cleaner per gallon (16-32 ml per liter) of water. Rinse and let dry. 3. Traffic Area: Clean with 2-4 oz. of Neutrum floor cleaner per gallon (16-32 ml per liter) of water. Rinse and let dry. Apply additional thin coats of Elite 22 floor finish to traffic lanes as needed. 4. Buffing: If desired, periodic burnishing with blended hair pads will enhance appearance. 5. Periodic Complete Maintenance: Ordinarily, stripping is not required more than (1) or (2) times per year. Use up to 32 oz. of Mr. Xcel stripper per gallon (256 ml per liter) of water.

### SPECIFICATIONS

Form: Opaque Liquid  
Color: Milky White  
Flash Point: Closed cup: >200° F  
Odor: Bland  
Boiling Point: 212° F  
Melting Point: 32° F  
Solubility in Water: n/a  
Specific Gravity: n/a  
Volatile by Volume: n/a  
pH: 8.0 to 8.5  
Storage Stability: 1 Year +  
Evaporation Rate: n/a  
Vapor Density: <1  
VOC: 2.6%  
Viscosity: n/a  
Phosphate: none