

# Apollo (CC195\_4CS)

## High Speed Cleaner and Restorer

### LABEL INFORMATION

#### Apollo

APOLLO is a cleaner and restorer. Can be used on all resilient, stone, and wood floors that are finished to restore to like-new gloss while raising the slip co-efficient. This product is great for cleaning heavily soiled finished floors. Apollo eliminates restorer build-up and is slip-resistant.

#### USE ON

- Hard & Wood Floor
- Hard Floor
- Rubber & Wood Floor

#### USE IN

- Schools
- Hospitals
- Apartments
- Athletic Clubs
- Nursing Homes
- Restaurants
- Hotels/Motels

#### USE FOR

- High Speed Cleaning
- Restorer
- Floor Care

### FEATURES & BENEFITS

Mild pH (9.1 in dilution) - great for cleaning heavily soiled finished floors | Slip-resistant-UL classified | Pleasant citrus fragrance | Removes embedded soil and repairs scuffs, scratches, and dull spots while eliminating powdering

### DIRECTIONS

#### HARD & WOOD FLOOR CARE

CLEANER AND RESTORER - AUTO SCRUB AND BUFF: 1. Dilute at 6 ounces per gallon of water. 2. With an automatic scrubber and red pad, scrub floor area and pickup. 3. Allow floor to dry thoroughly. 4. Burnish floor with high speed machine and appropriate pad (hogs hair for wood). 5. Dust mop floor.

CLEANER AND RESTORER - MOP AND BUFF: 1. Dilute at 6 ounces per gallon of water. 2. With a mop and bucket, damp mop floor. 3. Allow floor to dry thoroughly. 4. Burnish floor with high speed machine and pad (hogs hair for wood). 5. Dust mop floor.

RESTORER - SPRAY BUFF: 1. Dilute at 2-4 ounces per quart of water. 2. Spray fine mist on area of floor (about 800 sq. ft./73 m<sup>2</sup>). 3. Let stand for 5 minutes until slightly damp but not completely dry. 4. Burnish floor with high speed machine and pad (hogs hair for wood). 5. Flip pad and buff to high gloss. 6. Dust mop floor.

#### HARD FLOOR CARE

DEEP SCRUB (prior to recoating): 1. Dilute 8 ounces per gallon of water. 2. Apply with mop and scrub with single disk machine or apply and scrub with an auto scrubber and blue pads. 3. Rinse floor thoroughly with Blue Magik (2 oz. per gallon/64 ml per liter) and allow to dry. 4. Apply 1 to 2 coats of floor finish.

STRIPPER: 1. Dilute at 10-12 ounces per gallon (80-96 ml per liter) of cold water. 2. Use conventional stripping methods.

#### RUBBER & WOOD FLOOR CARE

RUBBER/WOOD PREP (prior to recoating): 1. Dilute 8 ounces per gallon of water. 2. Apply product to floor in 200 ft<sup>2</sup> sections. Top scrub with maroon wood prep pad. 3. Pick up soiled solution and continue with 200 ft<sup>2</sup> sections until entire floor is deep cleaned. 4. Rinse floor thoroughly with Blue Magik (2 oz. per gallon) and allow to dry. 5. Apply finish following label directions.



### PACKING INFORMATION

Available in  
4x1 & 5 Gallon

### SPECIFICATIONS

Form: Liquid  
Color: Light Yellow  
Flash Point: Closed cup: >210° F  
Odor: Citrus  
Boiling Point: 212° F  
Melting Point: 32° F  
Solubility in Water: n/a  
Specific Gravity: 1.00  
Volatile by Volume: n/a  
pH: 9.7 to 10.7  
Storage Stability: 1 Year +  
Evaporation Rate: n/a  
Vapor Density: <1  
VOC: 1.4%  
Viscosity: n/a  
Phosphate: none