

Bullet™

Stub Out & Air Chamber

- Reduce job site and shop costs such as measuring, cutting, cleaning, fluxing, assembling and soldering
- Turn your variable job site costs into fixed job costs
- 1¼" - 2" CTS Bullets available for quote
- Accepts sweat, push-fitting and compression valves

Polished Nickel-Plated

- Eliminates the need for sleeving or tinning
- Solders with standard flux and solder

Bracketed Stub Out

- Perfect for stubbing up through the floor for closets or lavs
- Square O Strap is crimped to tube 12" from each end

| Item No | Copper Type | CTS | Length | Pkg | Min Qty | Case Qty |
|---------------|-------------|-----|--------|-----|---------|----------|
| STANDARD | | | | | | |
| 622-M06 | M | ½" | 6" | B | 100 | 100 |
| 622-M06PK | M | ½" | 6" | C* | 20 | 20 |
| 622-M08 | M | ½" | 8" | B | 100 | 100 |
| 622-M08PK2 | M | ½" | 8" | C* | 10 | 10 |
| 622-M10 | M | ½" | 10" | B | 100 | 100 |
| 622-M12 | M | ½" | 12" | B | 100 | 100 |
| 622-M12PK2 | M | ½" | 12" | C* | 10 | 10 |
| 622-M15 | M | ½" | 15" | B | 100 | 100 |
| 622-M18 | M | ½" | 18" | B | 100 | 100 |
| 622-M24 | M | ½" | 24" | B | 50 | 50 |
| 622-L06 | L | ½" | 6" | B | 100 | 100 |
| 622-L06PK | L | ½" | 6" | C* | 100 | 100 |
| 622-L08 | L | ½" | 8" | B | 100 | 100 |
| 622-L08PK | L | ½" | 8" | C* | 100 | 100 |
| 622-L10 | L | ½" | 10" | B | 100 | 100 |
| 622-L12 | L | ½" | 12" | B | 100 | 100 |
| 622-L15 | L | ½" | 15" | B | 100 | 100 |
| 622-L18 | L | ½" | 18" | B | 100 | 100 |
| 622-L24 | L | ½" | 24" | B | 50 | 50 |
| 623-L06 | L | ¾" | 6" | B | 50 | 50 |
| 623-L08 | L | ¾" | 8" | B | 50 | 50 |
| 623-L12 | L | ¾" | 12" | B | 50 | 50 |
| 623-L15 | L | ¾" | 15" | B | 50 | 50 |
| 623-L18 | L | ¾" | 18" | B | 50 | 50 |
| 623-L24 | L | ¾" | 24" | B | 50 | 50 |
| 624-L08 | L | 1" | 8" | B | 30 | 30 |
| 624-L12 | L | 1" | 12" | B | 30 | 30 |
| 624-L15 | L | 1" | 15" | B | 30 | 30 |
| 624-L18 | L | 1" | 18" | B | 30 | 30 |
| 624-L24 | L | 1" | 24" | B | 30 | 30 |
| NICKEL-PLATED | | | | | | |
| 622-L08N | L | ½" | 8" | B | 25 | 25 |
| BRACKETED | | | | | | |
| 622-L24E | L | ½" | 24" | B | 20 | 20 |



622-L08



622-L24E



622-L08N



Bullets™ save time and reduce on-the-job costs. Perfect for any stub out or air chamber application.



Leakproof

Spin closed ends have **five** times the wall thickness of the copper tube. Each fitting is factory inspected.



SUPPLY

DRAINAGE

SUPPORT

APPENDIX