## 2.2.2 FITTINGS

COMPONENT	MATERIAL	CSST X NPS	
Mechanical Joints Male Straight	Body: Brass Retainer: Brass Nut: Brass Gasket: Composite Fiber	10M (3/8") x 3/8 15M (1/2") x 1/2 20M (3/4") x 3/4 25M (1") x 1 32M (1 1/4") x 1 1/4 38M (1 1/2") x 1 1/2 50M (2") x 2	

COMPONENT	MATERIAL	CSST X NPS	400
Mechanical Joints Male Reducing	Body: Brass Retainer: Brass Nut: Brass Gasket: Composite Fiber	10M ( <sup>3</sup> /8") x <sup>1</sup> /2 15M ( <sup>1</sup> /2") x <sup>3</sup> /8 20M ( <sup>3</sup> /4") x <sup>1</sup> /2 25M (1") x <sup>3</sup> /4	

COMPONENT	MATERIAL	CSST X NPS	
Mechanical Joints Female Straight	Body: Brass Retainer: Brass Nut: Brass Gasket: Composite Fiber	15M ( <sup>1</sup> /2") x <sup>1</sup> /2 20M ( <sup>3</sup> /4") x <sup>3</sup> /4 25M (1") x 1	

COMPONENT	MATERIAL	CSST X NPS	
Mechanical Joints Female Reducing	Body: Brass Retainer: Brass Nut: Brass Gasket: Composite Fiber	10M ( <sup>3</sup> /8") x <sup>1</sup> /2 15M ( <sup>1</sup> /2") x <sup>3</sup> /8 20M ( <sup>3</sup> /4") x <sup>1</sup> /2 25M (1") x <sup>3</sup> /4	

