





WELLXTROL

Next Generation Well Tanks Featuring Antimicrobial Protection

Specifications



Model Number	Tank Volume (Gallons)	Max. Acceptance Factor	Dimensions		System Conn. (Inches)	Drawdown (Gallons)			Shipping Weight (lbs.)
			A Diameter (Inches)	B Height (Inches)		30/50 (psig)	40/60 (psig)	50/70 (psig)	
WX-101	2.0	0.45	8	13	¾ NPTM	0.6	0.6	0.5	5
WX-102	4.4	0.55	11	15	¾ NPTM	1.4	1.2	1.0	9
WX-103	7.4	0.43	11	22	¾ NPTM	2.4	2.0	1.8	15
WX-104	10.3	1.00	15	18	1 NPTM	3.2	2.8	2.4	20
WX-200	14.0	0.81	15	22	1 NPTM	4.3	3.8	3.3	22
WX-201	14.0	0.81	15	25	1 NPTF	4.3	3.8	3.3	25
WX-202	20.0	0.57	15	32	1 NPTF	6.2	5.4	4.7	32
WX-202XL	26.0	0.44	15	39	1 NPTF	8.0	7.0	6.1	39
WX-203	32.0	0.35	15	47	1 NPTF	9.9	8.6	7.6	47
WX-205	34.0	1.00	22	30	1 ¼ NPTF	10.5	9.1	8.0	57
WX-250	44.0	0.77	22	36	1 ¼ NPTF	13.6	11.8	10.4	65
WX-251	62.0	0.55	22	47	1 ¼ NPTF	19.2	16.6	14.6	87
WX-255	81.0	0.41	22	57	1 ¼ NPTF	25.0	21.7	19.1	109
WX-252	86.0	0.39	22	62	1 ¼ NPTF	26.6	23.0	20.3	107
WX-302	86.0	0.54	26	47	1 ¼ NPTF	26.6	23.0	20.3	106
WX-350	119.0	0.39	26	62	1 ¼ NPTF	36.8	31.9	28.1	146

Stainless Steel System Connection.

Maximum Working Pressure: All models except WX-252: 150 psig. WX-252: 100 psig. Factory Precharge: 38 psig. Drawdown can be affected by various ambient and system conditions, including temperature and pressure.