

PFX146

Stainless Steel and PVC Ice Maker

Reinforced Flexible Connectors



Product Features

- Working Temperature: 40°F to 140°F
- Working Pressure: up to 125 PSI maximum
- Internal Hose: reinforced PVC
- Outer Wire Braid: 304 stainless steel (not applicable to PVC connector – PFX146198)
- Barb: low lead brass alloy
- Metal Nuts: nickel-plated brass alloy
- Ferrule: nickel-plated brass alloy
- Washer: EPDM rubber



PFX146198

Installation Instructions

- For use with water in accessible locations only
- Metal Nuts: hand tighten plus 1/4 turn with wrench
- Do not over tighten nuts
- Check for leaks before leaving job site
- Inspect regularly for general fitness and replace if damaged, corroded or worn
- Do not expose to corrosive chemicals



PFX146205

Models and Product Certifications

| Model # | Description | cUPC | UPC | Low Lead Compliant |
|-----------|---|------|-----|--------------------|
| PFX146198 | 1/4" COMP X 1/4" COMP X 60" PVC Ice Maker | | ✓ | ✓ |
| PFX146202 | 1/4" COMP X 1/4" COMP X 24" SS Ice Maker | ✓ | ✓ | ✓ |
| PFX146205 | 1/4" COMP X 1/4" COMP X 60" SS Ice Maker | | ✓ | ✓ |
| PFX146207 | 1/4" COMP X 1/4" COMP X 84" SS Ice Maker | | ✓ | ✓ |

Warranty and Listing Certification

This PROFLO product carries a 1-year limited warranty.
IAPMO listed to ASME A112.18.6-2009 and CSA B125.6-2009
IAPMO listed to NSF/ANSI 61 and NSF/ANSI 372