

PFX146

Stainless Steel and PVC Toilet

Reinforced Flexible Connectors



Product Features

- Working Temperature: 40°F to 140°F
- Working Pressure: up to 125 PSI maximum
- Internal Hose: reinforced PVC
- Outer Wire Braid: 304 stainless steel (not applicable to PVC connector – PFX146172)
- Barb: low lead brass alloy
- Metal Nuts: nickel-plated brass alloy
- Ferrule: nickel-plated brass alloy
- Washer: Santoprene/EPDM rubber



PFX146172



PFX146463

Installation Instructions

- For use with water in accessible locations only
- Metal Nuts: hand tighten plus 1/4 turn with wrench
- Plastic Nuts: hand tighten only and do not use tools
- Do not over tighten nuts
- Check for leaks before leaving job site
- Inspect regularly for general fitness and replace if damaged, corroded or worn
- Do not expose to corrosive chemicals



PFX146472

Models and Product Certifications

| Model # | Description | cUPC | UPC | Low Lead Compliant |
|-----------|--|------|-----|--------------------|
| PFX146172 | 3/8" COMP X 7/8" BALLCOCK X 12" PVC Toilet | ✓ | ✓ | ✓ |
| PFX146462 | 1/2" FIP X 7/8" BALLCOCK X 12" SS Toilet | ✓ | ✓ | ✓ |
| PFX146463 | 1/2" FIP X 7/8" BALLCOCK X 16" SS Toilet | ✓ | ✓ | ✓ |
| PFX146471 | 3/8" COMP X 7/8" BALLCOCK X 9" SS Toilet | ✓ | ✓ | ✓ |
| PFX146472 | 3/8" COMP X 7/8" BALLCOCK X 12" SS Toilet | ✓ | ✓ | ✓ |
| PFX146473 | 3/8" COMP X 7/8" BALLCOCK X 16" SS Toilet | ✓ | ✓ | ✓ |
| PFX146474 | 3/8" COMP X 7/8" BALLCOCK X 20" SS Toilet | ✓ | ✓ | ✓ |
| PFX146492 | 1/2" COMP X 7/8" BALLCOCK X 12" SS Toilet | ✓ | ✓ | ✓ |

Warranty and Listing Certification

This PROFLO product carries a 1-year limited warranty.
IAPMO listed to ASME A112.18.6-2009 and CSA B125.6-2009
IAPMO listed to NSF/ANSI 61 and NSF/ANSI 372