


# Quarter-Turn Boiler Drains

125 lb. CWP to 100°F

Maximum Temperature 180°F

## QUARTER-TURN BOILER DRAINS MATERIAL LIST



PART	SPECIFICATION
Screw	Steel
I.D. Tag	Aluminum
Handle	Zinc
Stem	Brass ASTM B 16 UNS C36000
O-Ring	Nitrile
Seat	PTFE
Ball	Brass ASTM B 16 UNS C36000
Adapter	Brass ASTM B 283 UNS C37700
Body	Brass ASTM B 283 UNS C37700



**QT73X**

DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
BOILER DRAIN FIP to Hose	1/2	2.64"	1.57"	.42 lb
	3/4	2.72"	1.65"	.46 lb

IAPMO Listed to cUPC®



**QT74X**

DESCRIPTION	NOM. SIZE	DIMENSIONS		APPROX. NET WT.
		A	B	
BOILER DRAIN Cup or MIP Threads to Hose	1/2"	2.64"	1.57"	.40 lb
	3/4"*	2.72"	1.65"	.42 lb

IAPMO Listed to cUPC®

\* 3/4" furnished in male threads only

NOT FOR USE WITH POTABLE DRINKING WATER APPLICATIONS AFTER JANUARY 3, 2014.