2.2.2 FITTINGS

COMPONENT	MATERIAL	CSST X NPS	
Adapter Nut	Nut: Brass Locknut: Steel	10M (³ /8″) x 3/4 15M (¹ /2″) x 3/4 20M (³ /4″) x 1	
COMPONENT	MATERIAL	CSST X NPS	
Termination Fittings Male (Indoor and Outdoor*) *Outdoor models supplied with o-rings	Body: Brass Retainer: Brass Nut: Malleable Iron Gasket: Composite Fiber O-rings: EPDM Rubber	10M (³ /8") x ¹ /2 15M (¹ /2") x ¹ /2 20M (³ /4") x ³ /4 25M (1") x ³ /4 25M (1") x 1	
COMPONENT	MATERIAL	CSST X NPS	
Termination Fittings Female (Indoor and Outdoor*) *Outdoor models supplied with o-rings	Body: Brass Retainer: Brass Nut: Malleable Iron Gasket: Composite Fiber O-rings: EPDM Rubber	10M (³ /8") x ¹ /2 15M (¹ /2") x ¹ /2 20M (³ /4") x ³ /4 25M (1") x ³ /4	
COMPONENT	MATERIAL	CSST X NPS	
Flange Termination Fittings Male (Indoor and Outdoor*) *Outdoor models sup- plied with o-rings	Body: Brass Retainer: Brass Nut: Malleable Iron Gasket: Composite Fiber O-rings: EPDM Rubber	10M (³ /8") x ¹ /2 15M (¹ /2") x ¹ /2 20M (³ /4") x ³ /4 25M (1") x ³ /4 32M (1 ¹ /4") x 1 ¹ /4 38M (1 ¹ /2") x 1 ¹ /2 50M (2") x 2	
COMPONENT	MATERIAL	CSST X NPS	
Floor Flange Termination Assemblies Male	Body: Brass Retainer: Brass Nut: Malleable Iron Gasket: Composite Fiber	10M (³ /8") x ¹ /2 15M (¹ /2") x ¹ /2 20M (³ /4") x ³ /4 25M (1") x 1	

