

PIPE JOINT LUBRICANT

Product Features

- All purpose pipe lube can be used on most types of pipe including cast iron, ductile iron, carbon steel, stainless steel, concrete, clay, PVC, CPVC and more.
- Improved temperature range:
 - Spreads easily down to -10°F.
 - Stays stable up to 150°F
- Less odor
- Contains no petroleum, phosphate or silicone
- Will not support bacteria growth
- Biodegradable
- Non-toxic
- Smoother consistency — easier to spread
- Water dispersible — can be washed or rinsed from surfaces easily
- Minimal to no separation
- Clings well to most any surface

Pipe Diameter (inches)	Estimated Pounds of Lube per 100 Joints
4	3
6	4
6	4
10	5
12	6
15	10
18	12
21	14
24	16
27	18
30	30
36	26
42	31
48	37
54	42
60	50
66	57
72	64
78	70
84	78

*FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.

CALIFORNIA PROP 65 WARNING: This product may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **Wash Hands After Handling.**

PSLUBXL1Q
PSLUBXL1G
PSLUBXL5G



Directions for Use

- Clean all joint surfaces. Make certain that the gasket is properly positioned.
- Apply an even coating of lubricant to the inside of the bell and outside of spigot and gasket.
- Assemble the joint according to the pipe manufacturer's directions.

Product Specifications

Model Number	Description	Carton Weight
PSLUBXL1Q	Pipe Joint Lubricant	1 quart or 2 lbs
PSLUBXL1G	Pipe Joint Lubricant	1 gallon or 8 lbs
PSLUBXL5G	Pipe Joint Lubricant	5 gallons or 40 lbs

Certification and Approvals

- NSF/ANSI Standard 61 G compliant
- Complies with Calif. AB-1953 and Vermont Act 193
- FGG/BM/CZ™ System Compatible*

