



Proven Every Day // Proven Everywhere®

Slic-tite® Paste with PTFE

Premium Thread Sealant



USDA approved for use in federally inspected meat and poultry plants.

FEATURES:

- Slic-tite® contains more PTFE than other national brands. The higher concentration of PTFE particles provides greater sealing power on all tapered pipe threads including those that are damaged.
- Brushes easily on wet or oily threads.
- Sticks to hot, oily threads, will not run off. Ideal for use on production lines using high speed pipe threading machines.
- The non-toxic, non-drying formula will not harden or crack in the pipe joint. Provides easy disassembly and break out.
- Seals to high pressures: 10,000 PSI for Liquids, 3,000 PSI for Gases.
- Sealing temperature range: -50° to 500°F (-46°C to 260°C).
- Meets Fed. Spec. TT-S-1732
- Slic-tite contains a product made from PTFE and other PTFE resins to assure high performance.

TYPICAL APPLICATIONS:

- Slic-tite seals all types of pipe threads: steel, stainless steel, brass, aluminum, iron, and PVC, CPVC and ABS plastic.
- Recommended Services: water, natural gas, LP gases, steam, air, gasoline, kerosene, Refrigerants, ammonia, caustics, and acids. Contact factory for specific use recommendations. NOT RECOMMENDED FOR USE WITH OXYGEN SERVICE. Use OXY-TITE®.



FGG/BM®, FlowGuard Gold®, BlazeMaster® and Corzan® are registered trademarks of The Lubrizol Corporation.



RECOMMENDED INDUSTRIES:

- Plumbing
- AC/R
- Industrial Piping
- Chemical Processing Plants
- Manufacturing Plants
- Gas Utilities
- Fire Sprinkler Piping
- Irrigation Systems

ORDERING INFORMATION

Part No.	Size	QTY/Case	Part No.	Size	QTY/Case
41209	1/4 pt. BIC	12	42013	1 qt. Flat Top	12
42009	1/4 pt. BIC	24	42049	1 qt. BIC	12
41219	1/2 pt. BIC	12	42014	1 gal.	4
42019	1/2 pt. BIC	24	42015	5 gal.	1
42012	1 pt. Flat Top	24	42069	55 gal.	1
42029	1 pt. BIC	24			

BIC = Brush in Cap

LP97R00010



Call, write or email for additional information

LA-CO Industries Inc.
1201 Pratt Boulevard
Elk Grove Village, Illinois 60007-5746
1-800-621-4025 • 1-847-956-7600 • Fax: 1-800-448-5436
www.laco.com
Email: customer_service@laco.com
Family owned and operated since 1934