

Kwikset Security Deadbolt Specifications

Kwikset Security Deadbolt Specifications

Door Prep	660, 665: Crossbore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4" 663: Crossbore 1-5/8" Edge Bore 1" Latch Face 1" x 2-1/4" 667: Crossbore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"
Backset	660, 665, 667: Adjustable latch standard. 663: 2-3/8" standard. 2-3/4" optional.
Door Thickness	660, 663, 665, 667: 1-3/8" – 1-3/4" doors standard.
Cylinder	660, 665: 5-pin.
Faceplates	660, 663, 665, 667: 1" x 2-1/4" square corner standard. Round corner and other options available.
Strikes	660, 663, 665, 667: 1" x 2-1/4" square corner standard. Round corner and other options available.
Bolt	1" throw.
Door Handing	Reversible for right- or left-hand doors.
ANSI/BHMA	660, 663, 665, 667: A156.5 Grade 3.

Kwikset Security Deadbolt Dimensions

Dimensions	Design	A	B	C	D	E	F
	660	2-1/2"	1-1/8"	2-1/2"	1"	3/8"	1-3/4"
	665	2-1/2"	1-1/8"	2-1/2"	1-1/8"		
	663			2-1/2"	1"	3/4"	1-3/4"
	667	2-1/2"	3/8"	2-1/2"	1"	3/8"	1-3/4"
	677	2-1/2"	3/8"	2-1/2"	1"	3/8"	1-3/4"

Kwikset Security Deadbolt Finishes

Finish	3	5	15	15A	26	26D
660, 665	•	•	•	•	•	•
663	•	•	•			•
664, 667	•	•				•
677	•	•			•	•

Kwikset Security Function Descriptions

Function	Model	Description
	660	Single Cylinder: Deadbolt operated by key outside and thumbturn inside.
	665	Double Cylinder: Deadbolt operated by key both sides.
	663 <i>E0193</i>	Thumbturn only: Deadbolt operated by thumbturn one side. No trim on other side.
	664	Conversion Kit: Converts 663 to 667 when door is bored through.
	667 <i>E0193</i>	Thumbturn x Plate: Deadbolt operated by thumbturn on interior. Blank plate on exterior.
	677 <i>E0193</i>	Thumbturn x Plate: Deadbolt operated by thumbturn on interior. Blank plate on exterior. UL Listed.

Note: ANSI functions are listed in italics.

