



# PFXEM Series Frost Proof Yard Hydrants

## Product Features

- Lever control with variable flow
- Heavy-duty solid no lead brass hose adapter
- Pipe and rod are galvanized to prevent rust
- Head and lever can be padlocked when not in use to prevent unauthorized use
- Metal gland and packing nut included
- Drains below the frost line once hydrant is shut off
- Inlet: 3/4" NPT in no lead brass casting
- Outlet: 3/4" no lead brass hose thread
- Graphite packing
- Steel and molded rubber plunger made of self-lubricating material
- 1" galvanized pipe
- Overall length is 28" plus bury depth (bury depth is stenciled on pipe)

## Parts Available

**PFXEMHDL** - Lever control (A)

### PFEM7500RK

Repair Kit for PFEM7500 Series Yard Hydrant includes one each of the following:

- Draw straps (pair)
- Valve stem packing
- Pivot connector and nuts
- Plunger
- Packing nut

	DESCRIPTION	OVERALL LENGTH (INCHES)
PFXEM7501	1 FT BURY FREEZELESS YARD HYDRANT	39.5
PFXEM75015	1-1/2 FT BURY FREEZELESS YARD HYDRANT	45.5
PFXEM7502	2 FT BURY FREEZELESS YARD HYDRANT	51.5
PFXEM7503	3 FT BURY FREEZELESS YARD HYDRANT	63.5
PFXEM7504	4 FT BURY FREEZELESS YARD HYDRANT	75.5
PFXEM7505	5 FT BURY FREEZELESS YARD HYDRANT	87.5
PFXEM7506	6 FT BURY FREEZELESS YARD HYDRANT	99.5
*PFXEM7508	8 FT BURY FREEZELESS YARD HYDRANT	123.5
*PFXEM7510	10 FT BURY FREEZELESS YARD HYDRANT	147.5


\*For Canada only

WATER SYSTEM PRESSURE	GALLONS PER MINUTE ( GPM )									
	0	5	10	15	20	25	30	35	40	45
20 PSI	15.4 GPM @ 20 PSI									
30 PSI	18 GPM @ 30 PSI									
40 PSI	22 GPM @ 40 PSI									
60 PSI	27 GPM @ 60 PSI									
80 PSI	32 GPM @ 80 PSI									
100 PSI	36 GPM @ 100 PSI									
NOTE: Most common 1/2 hp submersible pumps output is 10 GPM.										




Made in U.S.A.

© 2015 Ferguson Enterprises, Inc. All Rights Reserved



## PFXEM SERIES

Low-Lead Compliant



- A - Lever Control
- B - Draw Straps
- C - Operating Rod
- D - Heavy-Duty Solid No Lead Brass Hose Adapter
- E - Heavy Cast Iron Head
- F - Pivot Connector with Stainless Steel Bolt
- G - Packing Gland
- H - Galvanized Pipe
- I - Long-life One Piece Plunger
- J - Double Bypass No Lead Valve Body
- K - Locking Eye

## Warranty and Codes

This PROFLO product carries a 1-year limited warranty.

Distributed Exclusively by Ferguson and Wolsley Canada

12483 06/15