# Figure XG GAUGES & THERMOMETERS



## LOW LEAD COMPLIANT 4-1/2" CONTRACTOR'S GAUGE

The contractor's gauge is designed for a wide variety of industrial applications, but is especially suited for heating and air conditioning systems. The rugged gauge case is made of stainless steel to provide the protection needed in corrosive atmospheres. Connection and wetted internal components meet Federal lead free requirements.

#### **Features:**

- Dual Scale (PSI and kPa)
- +/- 1% Grade 1A Per ANSI/ASME B40.100
- · Complies with Federal Lead-Free Law (Sec. 1417)
- 304SS Case and Bezel Ring
- Zero Adjustment Screw
- Lead Free Phosphor Bronze Bourdon Tube
- 1/4" Lead Free Brass MNPT Connection
- Brass Movement
- · Black Anodized Aluminum Pointer
- White Aluminum Dial with Black and Red Markings
- · Lead Free Silver Solder Welding
- · Acrylic Lens
- 75% of Full Scale Working Pressure
- 25% Over-Pressure Limit
- -40°F to 150°F (-40°C to 65°C) Process and Ambient Temperature Limit
- IP52 Enclosure Rating



Low Lead Compliant: Referring to laws defining "Lead Free" as wetted surface of pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤ 0.25% per the Safe Drinking Water Act (Sec. 1417) amended 1-4-2011 as well as other state regulations.



#### **Dial Resolution**

Range (PSI)	PSI Per Mark
0 to 30	0.5
0 to 60, 100	1
0 to 160, 200	2
0 to 300	5

### **Part Numbers**

Range (PSI)	Part Number
0 to 30	FNWXG030R
0 to 60	FNWXG060R
0 to 100	FNWXG0100R
0 to 160	FNWXG0160R
0 to 200	FNWXG0200R
0 to 300	FNWXG0300R

3.67 0.73 0.73 1.19 1/4" MNPT

DOC: FNWXG13 Ver. 10/2013

www.fnw.com

<sup>© 2013 -</sup> FNW. All rights reserved.
The FNW logo is a trademark of Ferguson Enterprises, Inc., PL Sourcing, PO Box 2778, Newport News, VA 23609