



# Flash 008

## Mechanical Key Duplicator

# Flash 008



**Smooth carriage movements** The space-saving rotating knob ensures precise horizontal movements. The carriage can also be easily moved manually using the front lever.



*Flash 008 is designed to cut typical residential, automotive and commercial keys including those with large bows or long blades such as cruciform keys as well as tip stop and flip-type keys.*

## Lightweight, compact and easy to operate

Flash 008 is easy to use and features long lasting materials and finishes. Lightweight and compact, it is perfect for small shops and mobile use.

## Four-sided clamps mean flexibility of use

Four-sided jaws easily clamp virtually all edge cut keys present on the market. Jaws are nickel coated to provide longer life. The jaws can be quickly and smoothly rotated by simply loosening the knob and rotating the jaw into the proper position.

3 1/2" (88.9 mm) spacing between the jaws accommodate large bow (head) and long blade keys including flip style automotive keys.



**Optimized calibration** A tracer point adjustment system provides fast, precise calibration.

## Wear resistant components

The cutter is AlTiN (Aluminum Titanium Nitride) coated for longer life and oxidation resistance even at temperatures up to 800°C (1,472°F). Teflon® coated bushings provide protection to the carriage shaft and guarantee a smoother, quieter movement.



## Space-saving solution for fixed or mobile use

Flash 008 is lightweight, compact and easily transportable. Secure the machine to the work counter with the mounting bracket (included).

**Operator safety** The on-off switch features a safety cut-out for user protection (machine must be manually re-started after a power interruption).

**Finish cut keys perfectly** The nylon de-burring brush bristles are perfect for the finishing of cut keys.

## Technical Data

<b>Power Supply:</b>	120V-60Hz
<b>Cutter motor:</b>	single phase and speed
<b>Movements:</b>	by rectified carriage shaft and rack
<b>Cutter:</b>	AlTiN coated HSS (Super Rapid Steel)
<b>Carriage Runs:</b>	1.65" (42 mm)
<b>Dimensions:</b>	Width: 12.2" (310 mm) Depth: 9.5" (240 mm) Height: 8.7" (220 mm)
<b>Weight:</b>	14 lbs (6.4 kg)

### Central America:

Mexico, Guatemala, Belize, El Salvador, Honduras, Nicaragua, Costa Rica, Panama

### Corporación Cerrajera Alba S.A. de C.V.

Prolongación avenida independencia 14, Bodega 5.  
Col. Los reyes, Tultitlán, Estado de México.  
C.P. 54915 • www.albailco.mx • Ph: 01.55.5366.7200

### North America:

U.S.A., Canada, Caribbean Islands

### Kaba Ilco Corp.

400 Jeffreys Road • Rocky Mount, NC 27804  
www.ilco.us • Ph: 800.334.1381 or 252.446.3321  
Fax: 252.446.4702

